

Front harrow

6.00 m



Spreading straw and residual plant.



Options:



Front harrow is a heavy duty front mounted harrow for establishing a "false" seed bed, spreading straw in the stubble and aerating grassland.



The front harrow is as standard equipped with 16 mm tines and the 2 row version has a weight of 170kg per meter. The tines are set at a distance of 125 mm achieving an efficient cultivation over the complete working width.



To obtain an exact depth and an efficient cultivation the front harrow is equipped with a turnable wheel and a mechanical adjustment of the tines on each row.



As an option the front harrow can be extended from 2 to 4 rows for ensuring an optimum under frame clearance and an optimum spreading of the residual plant.

Technical specifications:

Type (2-row)	300	400	500 H	600 H
Working width	3 m	4 m	5 m	6 m
HP required	30 HP	40 HP	50 HP	60 HP
Transport width	3 m	4 m	2,4 m	2,4 m
Nos of tines	24 pcs.	32 pcs.	40 pcs.	48 pcs.
Weight	510 kg	680 kg	850 kg	1020 kg
Distance of tines	125 mm	125 mm	125 mm	125 mm
Distance of row	600 mm	600 mm	600 mm	600 mm

Extension from 2 to 4 has a weight of 65 kg/meter

DAL-BO A/S

DAL-BO A/S | Bindeballevej 69 | DK-7183 Randbøl
Tlf.: +45 75 88 35 00 | Fax: +45 75 88 31 57
E-mail: info@dal-bo.dk | www.dal-bo.dk

